

A productivity booster that pays off.

These two devices are ready to become key players in your office. With a print speed of 40 pages per minute, short first print and first copy times and professional scanning features, including simultaneous scanning of both document sides, they will surely help boost the productivity in their respective workgroups.



ECOSYS M2040dn



Up to 40 pages per minute in A4

1,200 dpi printing quality

Dual scan document processor

Specifications

ECOSYS

ECOSYS stands for ECOlogy, ECONomy and SYStem-printing. With their longlife components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables. The cartridgefree system means that toner is the only consumable. The modular design concept allows you to add workflow enhancing functions as required. Integrated system software provides long-term cross network compatibility. KYOCERA's long-life components cost you and the environment less.

Environmental print features

Duplex print mode (Double sided printing), N-Up printing mode (N pages on 1 sheet), Toner save mode (Draft print mode), Quiet mode (reduced print speed).

KYOCERA NetViewer

KYOCERA NetViewer enables complete monitoring and control of all ECOSYS printers and digital KYOCERA multifunction units from any Windows® PC and thus provides ideal network administration. It also supports the standardised SNMP protocol.

ECOSYS M2040dn/ECOSYS M2540dn

GENERAL

Technology: KYOCERA ECOSYS Laser
Control panel display: 5 line LCD display
Engine speed: Up to 40 pages A4 per minute
Resolution: 300 dpi, 600 dpi, 1,200 dpi
Warm-up time: Approx. 17 seconds or less
Time to first print: Approx. 6.4 seconds or less
Time to first copy: Approx. 6.4 seconds or less
CPU: 800 MHz
Memory: Standard 512 MB, max. 1,536 MB
Standard interface: USB 2.0 (Hi-Speed), USB Host Interface, Gigabit Ethernet (10BaseT/100BaseTX/1000BaseT), Slot for optional SD/SDHC-Card
Dimensions (W x D x H): Main unit: 417 x 412 x 437 mm
Weight: Main unit: Approx. 19 kg
Power source: AC 240 V, 50 Hz
Power consumption:
Copy/Print: 661 W
Ready mode: 21 W
Sleep-mode: 1 W
Noise (Sound pressure level: ISO 7779/ISO 9296): Copy/Print: 48.3 dB(A) LpA
Quiet mode: 44.1 dB(A) LpA
Ready/Standby mode: Immeasurably low
Sleep mode: Immeasurably low
Safety standards: AS/NZS3260
This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.
Input capacity: 100-sheet multi-purpose tray; 60 – 220 g/m²; A4, A5, A6, B5, B6, Letter, Legal, Custom (70 x 148 mm – 216 x 356 mm) 250-sheet universal cassette; 60 – 163 g/m²; A4, A5, A6, B5, Letter, Legal, Custom (105 x 148 – 216 x 356 mm). Max. input capacity with options: 850 sheets
Duplex functionality as standard: Double-sided printing: 60 – 163 g/m²; A4, A5, B5, Letter, Legal

Command Center RX

The Command Center RX enables to control and manage various settings by accessing the device via Web browser.

USB Host Interface for USB Flash Memory

Documents can be printed directly from a USB Flash Memory (e.g. USB stick) via the USB host interface. The documents stored as PDF, XPS, TIFF or JPEG are selected directly via the printer's control panel. No computer is required.

Application-based Profiles

The KX printer driver can create a direct link between dedicated applications and predefined or customised print profiles. You can set that all documents from a user or an application be printed with activated duplex mode as standard, thus leading to a reduced paper consumption.

Dual scan document processor: 50-sheet, 50–160 g/m², A4, A5, A6, B5, B6, Letter, Legal, Custom (100 x 148 to 216 x 356 mm)
Output capacity: Max. 150 sheet face down with paper full deflection

PRINT FUNCTIONS

Controller language: PRESCRIBE IIc
Emulations: PCL 6 (PCL 5e/PCL-XL), PostScript 3 (KPDL 3), PDF Direct Print, XPS/OpenXPS
Operating systems: All current Windows operating systems, MAC OS X Version 10.5 or higher, Unix, Linux as well as other operating systems on request
Fonts/barcodes: 93 scalable fonts for PCL6/KPDL3, 8 fonts for Windows Vista, 1 bitmap font, 45 barcodes (e.g. EAN8, EAN13) with automatic generation of checksums as well as support of two-dimensional barcodes PDF-417 under PRESCRIBE (PCL and other barcodes available as an option)

COPY FUNCTIONS

Max. original size: A4(Platen)/Legal(DP)
Continuous copying: 1 – 9 99***
Zoom range: 25 – 400% in 1% steps
Preset magnification ratios: 7 Reductions/5 Enlargements
Exposure mode: Manual: 9 steps
Image adjustments: Text + Photo, Photo, Text, Map
Features: Scan-once-copy-many, electronic sort, 2in1, 4in1, ID-card copy, priority print, program, continuous scan, auto cassette change, copy density control

SCAN FUNCTIONS

Functionality: Scan-to-e-mail (SMTP), Scan-to-FTP (FTP over SSL), Scan-to-SMBv3, Scan to USB Host, TWAIN scan (USB, network), WSD (WIA) scan (USB, network)
Scan speed: 40 ipm (300 dpi, A4, b/w, simplex), 23 ipm (300 dpi, A4, colour, simplex), 32 ipm (300 dpi, A4, b/w, duplex), 16 ipm (300 dpi, A4, colour, duplex)
Scan resolution: 300dpi x 300dpi, 200dpi x 200dpi(Default), 200dpi x 100dpi, 600dpi x 600dpi, 400dpi x 400dpi, 200dpi x 400dpi
Max. scan size: A4(Platen), Legal(DP)
Original recognition: Text + Photo, Photo, Text, Light Text/ Fine Line, Text (for OCR)

Scan file formats: TIFF, PDF, PDF/A-1, high compression PDF, encrypted PDF, JPEG, XPS
Compression method: MMR/JPEG
Features: Integrated address book, LDAP, encrypted data transfer, Blank sheet skip

CONSUMABLES

Average continuous toner yield in accordance with ISO 19752

Toner-Kit TK-1174: toner yield 7,200 pages A4
Starter toner: toner yield 3,600 pages A4

OPTIONS

PF-1100 Paper feeder (max. 2 units): 250 sheets; 60 – 163g/m²; A4, A5, A6, B5, Letter, Legal, Custom (105 x 148 mm – 216 x 356 mm)

Memory upgrade: DIMM-1GBE: 1,024 MB

UG-33: ThinPrint support

USB IC Card Reader + Card Authentication Kit (B): Support for various authentication keys available

WARRANTY

2 years Return-to-base as standard.
Optional upgrade to On-site available.

Their low TCO makes them a very affordable and reasonable choice. Toner and paper capacity are equally impressive too, with up to 7,200 pages from one toner cartridge and up to 850 pages with two optional paper feeders. And as is to be expected from any KYOCERA device, they are extremely reliable, meaning you can stay productive as long as you need to.



KYOCERA Document Solutions Australia

Ph: 13 59 62

www.kyoceradocumentsolutions.com.au



Kyocera Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.
KYOCERA Document Solutions Australia Pty. Ltd ABN 77 003 852 444

KYOCERA Document Solutions Partner

DEC2022/ECOSYSM2040dn/M2540dn

KYOCERA Document Solutions New Zealand

Ph: 0800 459 623

www.kyoceradocumentsolutions.co.nz

kyoceradocumentsolutions.com.au